



BE PROTECTED  
THE GLOVE TO MATCH  
YOUR NEEDS.

GSBSERIES

SEE IT : FEEL IT : GLOVE IT



# GSB S02



**AL Glove Systems GSB S02 gloves**, made of Bromo-Butyl-Rubber (IIR), with high gas impermeability, high resistance to a wide range of toxins, polar hydrocarbons such as, acids, esters, ketones, and amine derivatives. They are highly sensitive and provides the best dexterity. Material thickness 0,2 mm  
The GSB S02 Glove is classified as PAH-free.

#### FEATURES:

##### ✦ Impermeable to gas

High resistance to the permeation of mainly oxygen, nitrogen, inert gases, etc. during production under inert gas atmosphere in inert boxes of the production of electronic components and microcomponents.

##### ✦ Flexible

Offers high sensitivity and the best dexterity in handling.

##### ✦ Resistant to chemicals

High resistance to a wide range of chemicals and toxins


#### SPECIFICATIONS

Material	Bromo-Butyl-Rubber (IIR) PAK [polycyclic aromatic hydrocarbons] -free
Colour	Black
Packaging	Single packaging in black PE bags
Recommended storage time	42 months
Application range	Inertboxes, Gloveboxes, Containment Chambers
Field of application	Production of electronic components, lamps, LEDs, Semiconductors, Nuclear applications, various research applications, Metal and Plastic 3D printing, Cytostatics production and handling, Chemical protection
Temperature application range:	- 40 °C to + 90 °C
Conductivity	antistatic (<math>10^8 \Omega</math>)
Gauntlet diameter*	150 mm, 160 mm, 180 mm, 200 mm, 225 mm, 250 mm, 300 mm
Size*	M (8), L (9-10), XL (11)
Hand shape	ambidextrous
Material thickness	0,2 mm
Length*	800 mm, 920 mm
Bead thickness	5 mm
Types	One-piece gloves, Sleeve with adapter ring

\* not all combinations immediately available, please contact us for more information

#### PARAMETERS AND TOLERANCES

Material thickness	-0,1 mm / +0,15 mm
Glove lengths	+/- 20 mm
Bead thickness	+/-0,5 mm




#### PERMEATION EN ISO 374-1:2016/A1:2018

A Methanol	Protection Level 6
B Acetone	Protection Level 6
K Sodium hydroxide 40%	Protection Level 6
L Sulphuric acid 96%	Protection Level 6
O Ammonium hydroxide 25%	Protection Level 6
T Formaldehyde 37%	Protection Level 6



SEE IT:   
FEEL IT: **GLOVE IT**

Follow us on 

AL Glove Systems GmbH • In der Dieterswiese 8 • 64653 Lorsch | Germany  
T +49 6251 82 669-0 • [info@alglobalsystems.de](mailto:info@alglobalsystems.de)

AL Glove  
Systems 

[www.alglobalsystems.de](http://www.alglobalsystems.de)