



BE PROTECTED
THE GLOVE TO MATCH
YOUR NEEDS.

GSE SERIES

SEE IT : FEEL IT : GLOVE IT



GSE DUO



AL Glove Systems GSE Duo Gloves

made of Ethylene Propylene Diene Rubber (EPDM) black/white show high resistance to most disinfectant chemicals.

The elastomer EPDM is resistant to alcohols as well as to acids and alkalis. It also shows good resistance to aging and weathering. Due to its temperature resistance up to 130°C, it is also suitable for steam sterilization.

FEATURES:

✦ Resistant to disinfection chemicals

Resistant to the commonly used chemicals for disinfection in production plants

✦ UV and ozone resistant

The gloves can withstand intense lighting situations.

✦ Fully electrically conductive

on the user side to avoid electrical charging by slipping in and out of the Gloves. The gloves can be used with grounded port Systems

✦ According to EU GMP guidelines Annex 1

Contamination Control Strategy (CCS) two color Glove, black inside / white outside for easy visual inspection

SPECIFICATIONS

Material	Ethylene Propylene Diene Rubber (EPDM)
Colour	Black inside / White outside
Packaging	Single packaging in black PE bags
Recommended storage time	42 months
Application range	Isolators, Gloveboxes, Restricted Access Barrier Systems (RABS)
Field of application	pharmaceutical industry, life science and biosciences, nuclear industry, various research applications
Temperature application range	- 40 °C to + 130 °C
Sterilisation	Gamma Radiation, VHP, Autoclaving
Conductivity	innerside fully conductive (10^{-6} Ohm)
Gauntlet diameter*	150 mm, 160 mm, 180 mm, 200 mm, 225 mm, 250 mm, 300 mm
Size*	M (8), L (9-10), XL (11)
Hand shape	ambidextrous
Material thickness	0,4 mm
Length*	800 mm, 920 mm
Bead thickness	5 mm
Types	One-piece gloves, Sleeve with adapter ring

* not all combinations immediately available, please contact us for more information

PARAMETERS AND TOLERANCES

Material thickness	-0,1 mm / +0,15 mm
Glove lengths	+/- 20 mm
Bead thickness	+/-0,5 mm



PERMEATION EN ISO 374-1:2016/A1:2018


P Hydrogen peroxide 30%	Protection Level 6
-------------------------	--------------------

MECHANICAL PROPERTIES EN 388:2016+A1:2018

Abrasion resistance	Protection Level 3
Cut resistance	Protection Level 0
Tear resistance	Protection Level 0
Puncture resistance	Protection Level 0
ISO cut resistance	Protection Level 0



SEE IT: 
FEEL IT: **GLOVE IT**

Follow us on 

AL Glove Systems GmbH • In der Dieterswiese 8 • 64653 Lorsch | Germany
T +49 6251 82 669-0 • info@alglobalsystems.de

