

# **GSE**



#### **AL Glove Systems GSE Gloves**

made of Ethylene Propylene Diene Rubber (EPDM) show high resistance to most disinfectant chemicals.

The elastomer EPDM is resistant to alcohols as well as to acids and alkalis. It also shows good resistance to aging and weathering. Due to its temperature resistance up to 130°C, it is also suitable for steam sterilization.

#### **FEATURES:**

# • Resistant to disinfection chemicals

Resistant to the commonly used chemicals for disinfection in production plants

# O UV and ozone resistant

The gloves can withstand intense lighting situations.

# • Fully electrically conductive

The gloves can be used with grounded port systems, which prevents for example powder adhesions due to static charging

#### **SPECIFICATIONS**

Material	Ethylene Propylene Diene Rubber (EPDM)	
Colour	Black	
Packaging	Single packaging in black PE bags	
Recommended storage time	42 months	
Application range	Isolators, Gloveboxes, Restricted Access Barrier Systems (RABS)	
Field of application	pharmaceutical industry, life science and biosciences, nuclear industry, various research applications	
Temperature application range	- 40 °C to + 130 °C	
Sterilisation	Gamma Radiation, VHP, Autoclaving	
Conductivity	fully conductive (<10^6 Ohm)	
Gauntlet diameter*	150 mm, 160 mm, 180 mm, 200 mm, 225 mm, 250 mm, 300 mm	
Size*	M (8), L (9-10), XL (11)	
Hand shape	ambidextrous	
Material thickness	0,4 / 0,6 mm	
Length*	800 mm, 920 mm	
Bead thickness	5 mm	
Types	One-piece gloves, Sleeve with adapter ring	

 $<sup>\</sup>mbox{\ensuremath{^{\star}}}$  not all combinations immediately available, please contact us for more information

#### **PARAMETERS AND TOLERANCES**

Material thickness	-0,1 mm / +0,15 mm
Glove lengths	+/- 20 mm
Bead thickness	+/-0,5 mm













# **PERMEATION** EN ISO 374-1:2016/A1:2018

P Hydrogen peroxide 30% Protection Level 6

#### **MECHANICAL PROPERTIES** EN 388:2016+A1:2018

Abrasion resistance	Protection Level 2
Cut resistance	Protection Level 0
Tear resistance	Protection Level 1
Puncture resistance	Protection Level 0
ISO cut resistance	Protection Level X







